

Product Highlights

Easy expansion

Quickly add two USB 3.0 ports and one USB Type-C port to any PC, allowing you to connect more peripherals with ease.

Dual Slot SD Card Reader

Dual slot SD card reader is compatible with both SD and microSD cards.

Compact and portable

Fits easily into any bag for travel and can still function even without a power adapter.



DUB-2325

Hub with two USB 3.0 ports, USB Type-C port, SD and microSD card slots and USB Type-C connector

Features

Connectivity

- Two USB 3.0 Type-A ports
- USB Type-C port (for data transmission only)
- SD card slot
- microSD card slot
- USB Type-C connector
- Backwards compatible with USB 2.0 and USB 1.1

Easy to Use

- Plug-and-play support
- Compact design
- Works on Windows, Mac, and Linux PCs

The D-Link DUB-2325 Hub with USB Type-C connector provides an easy way to connect up to three USB devices to your notebook or desktop computer and allows you to insert SD and microSD cards into the corresponding slots.

Add Three USB Ports to Your Computer

With the DUB-2325 Hub, you can conveniently add two USB 3.0 ports and one USB Type-C port to connect up to three USB peripheral devices to your PC. USB 3.0 technology supports data rates of up to 5 Gbps, which means that you can enjoy faster transfer speeds compared to previous USB standards.

Dual Slot SD Card Reader

The DUB-2325 Hub is equipped with the SD and microSD card slots. Use the dual slot card reader to access data on a SD and microSD card simultaneously.

Plug-and-play support

Simply connect the DUB-2325 to any PC (you can also plug in the power adapter if it is necessary). It's that easy - no drivers or software installation is required.

Technical Specifications

Hardware

Interfaces	<ul style="list-style-type: none"> Two USB 3.0 Type-A ports One USB Type-C port (for data transmission only) SD card slot microSD card slot One USB Type-C connector
LEDs	<ul style="list-style-type: none"> Power LED

Network

Standards	<ul style="list-style-type: none"> USB 3.0 for Type-C USB 3.0 USB 2.0 USB 1.1 OHCI UHCI EHCI xHCI
Data rate	<ul style="list-style-type: none"> Up to 5 Gbps
Connectivity rules	<ul style="list-style-type: none"> Up to 127 devices Hub cascading
System requirements	<ul style="list-style-type: none"> Available USB Type-C port Windows XP/Vista/7/8/10, Mac OS, Linux

Physical Parameters

Dimensions (L x W x H)	<ul style="list-style-type: none"> 108 x 35 x 13.5 mm
------------------------	--

Environmental Conditions

Power input	<ul style="list-style-type: none"> From PC (USB bus powered) 5 V / 2 A DC power adapter (Micro-USB)
Temperature	<ul style="list-style-type: none"> Operating: 0 to 40 °C Storage: -20 to 70 °C
Humidity	<ul style="list-style-type: none"> Operating: 10% to 90% non-condensing Storage: 5% to 90% non-condensing

Order Information

Part Number	Description
DUB-2325	Hub with two USB 3.0 ports, USB Type-C port, SD and microSD card slots and USB Type-C connector